

IN THE CLAIMS:

Claims 1 - 77 (canceled)

Claim 78 (new) An apparatus for embossing a substantially continuous web of sheet material, including an embossing roll comprising:

an elongated core having first and second ends, said elongated core being formed of a substantially rigid material;

an elongated sleeve having an embossing pattern formed thereon, said elongated sleeve being formed of a material which is less rigid than said core, said elongated sleeve material having a hardness of less than 40 P&J; and

a positioning means for selectively positioning said sleeve with respect to said core,

wherein said elongated sleeve is releasably secured to said core such that said elongated sleeve is axially and circumferentially fixed with respect to said core when in operation and can be selectively axially removed from said core.

Claim 79 (new) The apparatus according to claim 78, wherein the elongated sleeve material has a hardness of less than 30 P&J.

Claim 80 (new) The apparatus according to claim 78, wherein the elongated sleeve material has a hardness of less than 20 P&J.

Claim 81 (new) The apparatus according to claim 78, wherein the elongated sleeve material has a hardness of approximately 10 P&J.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 82 (new) The apparatus according to claim 78, wherein said core is formed of steel.

Claim 83 (new) The apparatus according to claim 78, wherein said elongated sleeve is formed of a material selected from a group consisting of metallic alloys, ceramic, polymers, fiberglass, kevlar, vulcanized rubber and fiber reinforced resins.

Claim 84 (new) The apparatus according to claim 78, wherein said elongated sleeve is covered with a material selected from a group consisting of metallic alloys, ceramic, polymers, fiberglass, kevlar, vulcanized rubber and fiber reinforced resins.

Claim 85 (new) The apparatus according to claim 78, wherein said embossing pattern is formed in an outer surface of said sleeve.

Claim 86 (new) The apparatus according to claim 78, wherein said embossing pattern is engraved in said outer surface of said sleeve.

Claim 87 (new) The apparatus according to claim 78, wherein said embossing pattern is laser engraved in said outer surface.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 88 (new) The apparatus according to claim 78, wherein said embossing pattern includes embossing elements having curvilinear side walls, spherical surfaces and multiple elevations with respect to a reference surface.

Claim 89 (new) The apparatus according to claim 78, wherein said positioning means includes at least one axially extending bore and at least one radially extending bore intersecting said axially extending bore formed in said core for selectively communicating pressurized air to a surface of said core.

Claim 90 (new) The apparatus according to claim 78, wherein said sleeve is formed of an expandable material such that when pressurized air is passed to said surface of said core, said sleeve expands so as to be displaceable with respect to said core.

Claim 91 (new) The apparatus according to claim 78, wherein said core includes a plurality of radially extending bores intersecting said axially extending bore.

Claim 92 (new) The apparatus according to claim 91, further comprising a circumferential groove in a surface of said core interconnecting said radially extending passages.

Claim 93 (new) The apparatus according to claim 92, wherein said circumferential groove is 0.0625" to 0.1875" wide and 0.0625" to 0.1875" deep.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 94 (new) The apparatus according to claim 78, wherein an inner diameter of said sleeve is substantially constant.

Claim 95 (new) The apparatus according to claim 78, wherein an inner surface of said sleeve adjacent respective ends of said sleeve is tapered outwardly to facilitate positioning of said sleeve on said core.

Claim 96 (new) The apparatus according to claim 78, wherein said positioning means includes a frusto-conical outer surface of said core and a substantially complimentary frusto-conical inner surface of said sleeve and fixing means for axially securing said sleeve with respect to said core such that said sleeve can be axially received over said core.

Claim 97 (new) A system for selectively positioning an embossing roll, comprising:

providing an elongated core formed of a substantially rigid material;

providing an elongated sleeve having an embossing pattern formed thereon, the sleeve formed of a material less rigid than said core;

positioning the sleeve over the core; and

a means for communicating pressurized air from a central bore of the core to an outer surface of the core for forming an air cushion between the core and the sleeve, the air cushion capable of selectively expanding an inner surface of the sleeve with

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

respect to the core while sliding the sleeve along the core, the air at a pressure of at least about 100 p.s.i. to about 300 p.s.i.

Claim 98 (new) The system according to claim 97, wherein the pressure is provided at a pressure of from at least 150 p.s.i. to about 250 p.s.i.

Claim 99 (new) The system according to claim 97, wherein the pressure is provided at a pressure of approximately 200 p.s.i.

Claim 100 (new) The system according to claim 97, wherein the sleeve is laser engraved.

Claim 101 (new) The system according to claim 97, wherein the core is steel.

Claim 102 (new) The system according to claim 97, wherein the sleeve is formed of a material having a hardness of less than 40 P&J.

Claim 103 (new) The system according to claim 97, wherein the sleeve is formed of a material having a hardness of less than 30 P&J.

Claim 104 (new) The system according to claim 97, wherein the sleeve is formed of a material having a hardness of less than 20 P&J.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 105 (new) The system according to claim 97, wherein the sleeve is formed of a material having a hardness of approximately 10 P&J.

Claim 106 (new) The system according to claim 97, wherein said elongated sleeve is formed of a material selected from a group consisting of metallic alloys, ceramic, polymers, fiberglass, kevlar, vulcanized rubber and fiber reinforced resins.

Claim 107 (new) The system according to claim 97, wherein said elongated sleeve is covered with a material selected from a group consisting of metallic alloys, ceramic, polymers, fiberglass, kevlar, vulcanized rubber and fiber reinforced resins.

Claim 108 (new) A system for embossing a substantially continuous web of material comprising:

a supply means for supplying at least one substantially continuous web of material;

feed means for feeding said substantially continuous web of material;

embossing means for embossing a predetermined pattern in said web material;

and

a take-up means for taking-up said web material;

said embossing means comprising;

at least one elongated core formed of a substantially rigid material; and

a plurality of elongated sleeves each having an embossing pattern formed thereon, and each sleeve formed of a material having a hardness of less than 40 P&J;

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

a positioning means for selectively positioning said sleeve with respect to said core,

wherein said plurality of elongated sleeves are interchangeable with one another with each of said plurality of elongated sleeves being selectively secured to said core in accordance with the predetermined embossing pattern formed thereon.

Claim 109 (new) The system according to claim 108, wherein at least one of the sleeves has a hardness of less than 30 P&J.

Claim 110 (new) The system according to claim 108, wherein at least one of the sleeves has a hardness of less than 20 P&J.

Claim 111 (new) The system according to claim 108, wherein at least one of the sleeves has a hardness of approximately 10 P&J.

Claim 112 (new) The system according to claim 108, wherein the core is formed of steel.

Claim 113 (new) The system according to claim 108, wherein said elongated sleeve is formed of a material selected from a group consisting of metallic alloys, ceramic, polymers, fiberglass, kevlar, vulcanized rubber and fiber reinforced resins.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 114 (new) The system according to claim 108, wherein said elongated sleeve is covered with a material selected from a group consisting of metallic alloys, ceramic, polymers, fiberglass, kevlar, vulcanized rubber and fiber reinforced resins.

Claim 115 (new) The system according to claim 108, wherein said embossing pattern is engraved in an outer surface of said sleeve.

Claim 116 (new) The system according to claim 108, wherein said embossing pattern is laser engraved in said outer surface.

Claim 117 (new) The system according to claim 108, wherein said embossing pattern includes embossing elements having curvilinear side walls and spherical surfaces, and multiple elevations with respect to a reference surface.

Claim 118 (new) The system according to claim 108, wherein said positioning means includes at least one axially extending bore and at least one radially extending bore intersecting said axially extending bore formed in said core for selectively communicating pressurized air to a surface of said core.

Claim 119 (new) The system according to claim 108, wherein said sleeve is formed of an expandable material such that when pressurized air is passed to said surface of said core, said sleeve expands so as to be displaceable with respect to said core.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 120 (new) The system according to claim 108, wherein said core includes a plurality of radially extending bores intersecting said axially extending bore.

Claim 121 (new) The system according to claim 120, further comprising a circumferential groove in a surface of said core interconnecting said radially extending passages.

Claim 122 (new) The system as defined in claim 121, wherein said circumferential groove is 0.0625" to 0.1875" wide and 0.0625" to 0.1875" deep.

Claim 123 (new) The system as defined in claim 108, wherein an inner diameter of said sleeve is substantially constant.

Claim 124 (new) The system as defined in claim 108, wherein an inner surface of said sleeve adjacent respective ends of said sleeve is tapered outwardly to facilitate positioning of said sleeve on said core.

Claim 125 (new) The system as defined in claim 108, wherein said positioning means includes a frusto-conical outer surface of said core and a substantially complimentary frusto-conical inner surface of said sleeve and fixing means for axially securing said sleeve with respect to said core such that said sleeve can be axially received over said core.

F1
(continued)

Claim 126 (currently amended) A system for embossing a substantially continuous web of material comprising:

a supply means for supplying at least one substantially continuous web of material;

feed means for feeding said substantially continuous web of material;

embossing means for embossing a predetermined pattern in said web material;

and

a take-up means for taking-up said web material;

wherein at least one roll of the system includes;

an elongated core formed of a substantially rigid material;

an elongated sleeve formed of a material less rigid than said elongated core, the elongated sleeve material having a hardness of less than 40 P&J, with said elongated sleeve being releasably secured to said core such that said elongated sleeve is axially and circumferentially fixed with respect to said core when in operation and can be selectively axially removed from said core; and

a positioning means for selectively positioning said sleeve with respect to said core,

wherein said sleeve is formed of an expandable material such that when pressurized air is passed to said surface of said core, said sleeve expands so as to be displaceable with respect to said core and said sleeve includes an embossing pattern.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 127 (new) The system according to claim 126, wherein the elongated sleeve material has a hardness of less than 30 P&J.

Claim 128 (new) The system according to claim 126, wherein the elongated sleeve material has a hardness of less than 20 P&J.

Claim 129 (new) The system according to claim 126, wherein the elongated sleeve material has a hardness of approximately 10 P&J.

Claim 130 (new) The system according to claim 126, wherein said core is formed of steel.

Claim 131 (new) The system according to claim 126, wherein said elongated sleeve is formed of a material selected from a group consisting of metallic alloys, ceramic, polymers, fiberglass, kevlar, vulcanized rubber and fiber reinforced resins.

Claim 132 (new) The system according to claim 126, wherein said elongated sleeve is covered with a material selected from a group consisting of metallic alloys, ceramic, polymers, fiberglass, kevlar, vulcanized rubber and fiber reinforced resins.

Claim 133 (new) The system according to claim 126, wherein said sleeve includes an embossing pattern engraved in an outer surface of said sleeve.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 134 (new) The system according to claim 126, wherein said embossing pattern is laser engraved in said outer surface.

Claim 135 (new) The system according to claim 126, wherein said embossing pattern includes embossing elements having curvilinear side walls and spherical surfaces and multiple elevations with respect to a reference surface.

Claim 136 (new) The system according to claim 126, wherein said positioning means includes at least one axially extending bore and at least one radially extending bore intersecting said axially extending bore formed in said core for selectively communicating pressurized air to a surface of said core.

Claim 137 (new) The system according to claim 126, wherein said core includes a plurality of radially extending bores intersecting said axially extending bore.

Claim 138 (new) The system according to claim 137, further comprising a circumferential groove in a surface of said core interconnecting said radially extending passages.

Claim 139 (new) The system according to claim 138, wherein said circumferential groove is .0625" to .1875" wide and .0625" to .1875" deep.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 140 (new) The system according to claim 126, wherein an inner diameter of said sleeve is substantially constant.

Claim 141 (new) The system according to claim 126, wherein an inner surface of said sleeve adjacent respective ends of said sleeve is tapered outwardly to facilitate positioning of said sleeve on said core.

Claim 142 (new) The system according to claim 126, wherein said positioning means includes a frusto-conical outer surface of said core and a substantially complimentary frusto-conical inner surface of said sleeve and fixing means for axially securing said sleeve with respect to said core such that said sleeve can be axially received over said core.

Claim 143 (new) An apparatus for embossing a substantially continuous web of sheet material, including an embossing roll comprising:

an elongated core having first and second ends, said elongated core being formed of a substantially rigid material;

an elongated sleeve having an embossing pattern formed thereon, said elongated sleeve being formed of a material which is less rigid than said core; and

a positioning means for selectively positioning said sleeve with respect to said core, wherein said positioning means includes at least one axially extending bore and a plurality of radially extending bores intersecting said axially extending bore, wherein at least one substantially circumferential groove in a surface of said core interconnects the

distal ends of said radially extending passages, and wherein said radially extending bores are capable of communicating pressurized air from said core to said circumferential groove,

wherein said elongated sleeve is releasably secured to said core such that said elongated sleeve is axially and circumferentially fixed with respect to said core when in operation and can be selectively axially removed from said core.

Claim 144 (new) A system for selectively positioning an embossing roll, comprising:

providing an elongated core formed of a substantially rigid material;

providing an elongated sleeve having an embossing pattern formed thereon, the sleeve formed of a material less rigid than said core;

sliding the sleeve over the core; and

communicating pressurized air from a central bore of the core to an outer surface of the core for forming an air cushion between the core and the sleeve, the air cushion selectively expanding an inner surface of the sleeve with respect to the core while sliding the sleeve along the core,

wherein the pressurized air is communicated from said central bore to said outer surface of the core through a plurality of radially extending bores intersecting said axially extending bore, and wherein at least one substantially circumferential groove in a surface of said core interconnects the distal ends of said radially extending passages.

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

Claim 145 (new) A system for embossing a substantially continuous web of material comprising:

a supply means for supplying at least one substantially continuous web of material;

feed means for feeding said substantially continuous web of material;

embossing means for embossing a predetermined pattern in said web material;

and

a take-up means for taking-up said web material;

said embossing means comprising;

at least one elongated core formed of a substantially rigid material; and

a plurality of elongated sleeves each having an embossing pattern formed thereon;

a positioning means for selectively positioning said sleeve with respect to said core, wherein said positioning means includes at least one axially extending bore and a plurality of radially extending bores intersecting said axially extending bore, wherein at least one substantially circumferential groove in a surface of said core interconnects the distal ends of said radially extending passages, and wherein said radially extending bores are capable of communicating pressurized air from said core to said circumferential groove,

wherein said plurality of elongated sleeves are interchangeable with one another with each of said plurality of elongated sleeves being selectively secured to said core in accordance with the predetermined embossing pattern formed thereon.

F1
(continued)

Claim 146 (currently amended) A system for embossing a substantially continuous web of material comprising:

a supply means for supplying at least one substantially continuous web of material;

feed means for feeding said substantially continuous web of material;

embossing means for embossing a predetermined pattern in said web material;

and

a take-up means for taking-up said web material;

wherein at least one roll of the system includes;

an elongated core formed of a substantially rigid material;

an elongated sleeve formed of a material less rigid than said elongated core, with said elongated sleeve being releasably secured to said core such that said elongated sleeve is axially and circumferentially fixed with respect to said core when in operation and can be selectively axially removed from said core; and

a positioning means for selectively positioning said sleeve with respect to said core, wherein said positioning means includes at least one axially extending bore and a plurality of radially extending bores intersecting said axially extending bore, wherein at least one substantially circumferential groove in a surface of said core interconnects the distal ends of said radially extending passages, and wherein said radially extending bores are capable of communicating pressurized air from said core to said circumferential groove,

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP

1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com

wherein said sleeve is formed of an expandable material such that when pressurized air is passed to said surface of said core, said sleeve expands so as to be displaceable with respect to said core and said sleeve includes an embossing pattern.

Claim 147 (new) An apparatus for embossing a substantially continuous web of sheet material, including an embossing roll comprising:

an elongated core having first and second ends, said elongated core being formed of a substantially rigid material;

an elongated sleeve having an embossing pattern formed thereon, said elongated sleeve being formed of a material which is less rigid than said core; and

a positioning means for selectively positioning said sleeve with respect to said core, wherein said positioning means includes a substantially circumferential air curtain, and

wherein said elongated sleeve is releasably secured to said core such that said elongated sleeve is axially and circumferentially fixed with respect to said core when in operation and can be selectively axially removed from said core.

F1
(concluded)